



US007163255B2

(12) **United States Patent**
Rawlings et al.

(10) **Patent No.:** **US 7,163,255 B2**
(45) **Date of Patent:** **Jan. 16, 2007**

(54) **FOLDING CONVERTIBLE TOP WITH INTEGRAL BOOT**

(75) Inventors: **Stephen P. Rawlings**, Onsted, MI (US);
Albert W. Harrison, III, Detroit, MI (US)

(73) Assignee: **Dura Convertible Systems, Inc.**,
Adrian, MI (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

2,704,225 A	3/1955	Ansuetz et al.
2,768,024 A	10/1956	Spear, Jr.
2,919,156 A	12/1959	Dodge
3,271,067 A	9/1966	Rollman
3,375,037 A	3/1968	Hunt, Jr.
3,473,842 A	10/1969	Bracey et al. 296/116
3,536,354 A	10/1970	Ingram
3,655,238 A	4/1972	Stewart
3,666,317 A	5/1972	Podwys

(Continued)

(21) Appl. No.: **10/415,321**

FOREIGN PATENT DOCUMENTS

(22) PCT Filed: **Oct. 20, 2001**

CH 650 980 A5 8/1985

(86) PCT No.: **PCT/US01/49236**

(Continued)

§ 371 (c)(1),
(2), (4) Date: **Apr. 7, 2004**

Primary Examiner—Joseph D. Pape
(74) Attorney, Agent, or Firm—Brinks Hofer Gilson & Lione

(87) PCT Pub. No.: **WO02/43978**

PCT Pub. Date: **Jun. 6, 2002**

(57) **ABSTRACT**

(65) **Prior Publication Data**

US 2004/0232721 A1 Nov. 25, 2004

(51) **Int. Cl.**
B60J 7/00 (2006.01)

(52) **U.S. Cl.** **296/116**; 296/121; 296/107.08

(58) **Field of Classification Search** 296/107.01,
296/108, 116, 121, 107.08, 107.09, 107.15,
296/123

See application file for complete search history.


(56) **References Cited**

U.S. PATENT DOCUMENTS

505,544 A	9/1893	Tabor
652,090 A	6/1900	Daugherty et al.
1,184,734 A	5/1916	Freeman
1,952,252 A	3/1934	Heuser

A pair of side linkages for raising a convertible top (10) between a raised position, covering the vehicle body passenger compartment, through a body opening, and a lowered position folded into a storage compartment within the vehicle body, said top including a header (12) for engaging the vehicle windshield in the top raised position and at least one crossbow (14) extending between the side linkages, each linkage comprising side rails (18, 22) pivoted to and extending rearwardly from the header, and a plurality of links (34, 50, 56, 62) forming 4-bar linkages connecting the header (12), side rails (18, 22) and vehicle body for folding the top (10) in a Z-shaped folding action to a compact shape in the storage compartment such that the header (12) is not inverted and covers the folded top (10) and closes the body opening.

19 Claims, 7 Drawing Sheets



US 7,163,255 B2

Page 2

U.S. PATENT DOCUMENTS

3,690,722	A	9/1972	Bakewicz et al.	
3,823,977	A	7/1974	Fioravanti	
3,910,628	A	10/1975	Nantau	
3,917,337	A	11/1975	Couix	
3,994,524	A	11/1976	Lehmann	
4,286,821	A	9/1981	Cooper	
4,289,347	A	9/1981	Holzwarth	
4,346,930	A	8/1982	Northey	
4,487,447	A	12/1984	Schroder	
4,516,803	A	5/1985	Kaltz et al.	
4,553,784	A	11/1985	Trenkler	
4,621,861	A	11/1986	Scaduto	
4,626,020	A	12/1986	Kaltz et al.	
4,626,021	A	12/1986	Muscat	
4,693,509	A	9/1987	Moy et al.	
4,695,089	A	9/1987	Fukutomi et al.	
4,711,485	A	12/1987	Maebayashi et al.	
4,712,828	A	12/1987	Albrecht	
4,720,133	A	1/1988	Alexander et al.	
4,776,630	A	10/1988	Fukutomi et al.	
4,819,982	A	4/1989	Eyb	
4,842,327	A	6/1989	Hennessy	
4,854,634	A	8/1989	Shiraishi et al.	
4,895,409	A	1/1990	Konishi et al.	
4,915,443	A	4/1990	Uerlings et al.	
4,917,432	A	4/1990	Schrader et al.	
4,929,015	A	5/1990	Bauer	
4,948,194	A	8/1990	Dogliani	
4,950,022	A	8/1990	Pattee	
4,958,882	A	9/1990	Kolb	
4,964,668	A	10/1990	Hofmann	
4,969,679	A	11/1990	Eyb	
4,984,841	A	1/1991	Bauer et al.	
4,991,902	A	2/1991	Schrader et al.	
4,991,903	A	2/1991	Okabe et al.	
5,026,110	A	6/1991	Koop et al.	
5,029,932	A	7/1991	Parr	
5,078,447	A	1/1992	Klein et al.	
5,096,251	A	3/1992	Pfertner et al.	
5,154,479	A	10/1992	Sautter, Jr.	
5,207,474	A	5/1993	Licher et al.	296/107
5,320,400	A	6/1994	Orth et al.	
5,335,959	A	8/1994	Schrader et al.	
5,429,409	A	7/1995	Corder et al.	
5,593,202	A	1/1997	Corder et al.	

5,743,587	A	4/1998	Alexander et al.	
5,810,422	A	9/1998	Corder et al.	
D406,792	S	3/1999	Alexander et al.	
D427,138	S	6/2000	Alexander et al.	
6,207,143	B1	3/2001	Lezdey et al.	
D442,541	S	5/2001	Alexander et al.	
6,270,143	B1	8/2001	Heschhaus et al.	
D452,675	S	1/2002	Alexander et al.	
6,343,829	B1	2/2002	Busch	296/107.15
6,416,111	B1 *	7/2002	Neubrand	296/107.09
D464,605	S	10/2002	Alexander et al.	
6,692,061	B1 *	2/2004	Willard	296/116
RE38,546	E	7/2004	Corder et al.	
6,796,595	B1 *	9/2004	Doncov	296/107.09
2001/0040385	A1	11/2001	Obendiek	296/108
2002/0030381	A1	3/2002	Schutt et al.	296/108
2004/0232721	A1	11/2004	Rawlings et al.	

FOREIGN PATENT DOCUMENTS

DE	341652	10/1921
DE	464 440	8/1928
DE	629 252	4/1936
DE	646381	6/1937
DE	685 137	12/1939
DE	733757	4/1943
DE	885 356	8/1953
DE	756531	9/1956
DE	978638	12/1964
DE	31 27 525 A1	1/1983
DE	34 16 286 A1	4/1984
DE	3416286 A1	10/1984
DE	33 28 294 A1	2/1985
DE	3328294 A1	2/1985
DE	35 26 694 A1	12/1987
DE	38 09 197 A1	9/1989
DE	39 03 358 A1	8/1990
DE	44 38 191 C1	7/1995
JP	2-164615	6/1990
JP	2-306822	12/1990
JP	5-185844	7/1993
JP	6-226118	8/1994
JP	6-239322	8/1994
JP	62-31515	8/1994
JP	62-31516	8/1994

* cited by examiner




Fig. 1




Fig. 2




Fig. 3





Fig. 4






Fig. 7

1

FOLDING CONVERTIBLE TOP WITH INTEGRAL BOOT

TECHNICAL FIELD

This invention relates to vehicle convertible tops and, more particularly, to a top having a linkage which folds a top so that the header serves as a boot to cover the top when stored.

BACKGROUND OF THE INVENTION

Many different types of folding convertible soft and hard tops have been developed to enhance motoring pleasure by enabling a driver to selectively open and close the passenger compartment. These tops utilize a variety of different folding linkages, each of which are designed to accommodate the particular mechanical constraints of a specific vehicle application. It is desirable to utilize a top folding linkage that is simple, compact and stores the top in as little space as possible.

When these tops are lowered into a storage compartment, the header is normally inverted. This requires that the top or a portion of the top to be covered by a soft or hard boot to prevent accumulation of dust or other contaminants that would be dumped into the passenger compartment when the header rotates as the top is raised. The boot may be manually installed, or, is automatically manipulated by power operators, usually hydraulic cylinders. Installation of these boots requires time and/or effort to install. In the case of the soft boot, it requires separate storage when removed to enable the top to be raised.

It would be desirable to provide a convertible top that does not require a separate boot to close the top storage compartment, and incorporates a linkage, which stores the top in a compact configuration, with the outer surface of the header covering the remainder of the stored and folded top.

SUMMARY OF THE INVENTION

It is therefore an object of this invention to provide a convertible top that does not require a separate boot to close the top storage compartment, and incorporates a linkage, which stores the top in a compact configuration, with the exterior of the header covering the remainder of the stored and folded top.

Accordingly, this invention features a convertible top and a pair of side linkages for raising the top between a raised position, covering the vehicle body passenger compartment, through a body opening, and a lowered position folded into a storage compartment within the vehicle body. The top includes a cover, a header for engaging the vehicle windshield in top raised position, and at least one crossbow extending between the side linkages to support the cover in top raised position. Each side linkage includes a side rail pivoted to and extending rearwardly from the header and other links for folding the top in a Z-shaped folding action to a compact shape in the storage compartment such that the header is not inverted and covers the folded top and closes the body opening.

This invention also features 4-bar side linkages that enable the top to fold in the Z-shape.

Another feature of this invention is the use of a lost-motion connection between the header and a side rail to enable relative lateral movement during raising and lowering of the top.

2

These and other objects and features of this invention will become more readily apparent upon reference to the following detailed description of a preferred embodiment, as illustrated in the accompanying drawings, in which:

BRIEF DESCRIPTION OF THE DRAWINGS

FIGS. 1, 2, 3 and 4 are side views of a convertible top of this invention, sequentially shown in fully raised, $\frac{3}{4}$ raised, half raised, and fully lowered and stored position;

FIG. 5 is a perspective view of the top in its FIG. 3 position;

FIG. 6 an enlarged bottom detail view of the juncture of the header and the front side rail; and

FIG. 7 is an enlarged bottom view of a portion of FIG. 6, illustrating the flexible connection between the front side rail and the header.

DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring now to the drawings, a convertible top 10 has a conventional flexible fabric, or other similar material, cover (not illustrated) that is supported at its front by a plate-like extended header, or 1-bow, 12, and an intermediate bow 14. The cover for top 10 is conventionally attached to the vehicle body (not illustrated). Header 12 extends sufficiently rearward so as to incorporate what would normally be an intermediate 2-bow.

These supporting bows are pivotally connected at each side by an articulated linkage, which is conventionally operable by hydraulic cylinders, or other means (not shown) to raise and lower the top between an extended raised position covering the vehicle passenger compartment (not illustrated), as shown in FIG. 1, through the intermediate positions shown in FIGS. 2, 3 and 5, and a lowered and folded position, as shown in FIG. 4, within a storage compartment in a vehicle body (not illustrated).

Only one articulated side linkage is illustrated, since both are identical/symmetrical. The linkages comprise a front rail 16 that is secured to, and moves with header 12. A middle rail 18 has a forward extension 20 that is connected to front rail 16, as will be later described. A rear rail 22 is pivoted adjacent its lower end at 24 to the rod 26 of a hydraulic cylinder 28, which is pivoted at 30 to a body-mounted mounting bracket 32.

A lower control arm 34 is pivoted to bracket 32 at 36 and has an arm 38 that pivotally mounts one end 40 of a lower connecting link 42 that is pivoted at its other end 44 to the lower end 46 of rear rail 22. The upper end of lower control arm 34 is pivoted at 48 intermediate the ends of a middle connecting link 50 that has one end pivoted at 52 to middle rail 18 and its other end pivoted at 54 to an intermediate portion of rear rail 22.

The upper end of an upper connecting link 56 is pivoted at 58 to an intermediate portion of middle side rail 18, while its other end is pivoted to the upper end of rear rail 22 at 60. An upper control arm 62 is pivoted at 64 to a header-mounted bracket 66, and to an intermediate portion of upper connecting link 56 at 68.

The linkage just described, of course, is duplicated on the other side of the vehicle. It comprises three four-bar linkages that allow the top 10 to fold into a very compact, layered arrangement. As can be seen from viewing the folding sequence illustrated in FIGS. 1, 2, 3 and 4, top 10 folds into the form of a collapsed "Z". This is enabled by employing the four-bar linkages. The first linkage is formed by header

3

12, front rail 20, upper control arm 62 and the upper portion of upper connecting link 56, as defined by pivots 64, 68, 58 and the connection 70 between extension 20 of middle rail 18 and front rail 16.

The second four-bar linkage comprises upper connecting link 56, the lower portion of middle rail 18, middle connecting link 50 and the upper portion of rear rail 22, as defined by pivots 58, 52, 54 and 60. The third four-bar linkage is formed by the lower portion of middle connecting link 50, lower control arm 34, lower connecting link 42 and the lower portion of rear rail 22, as defined by pivots 48, 40, 44 and 54.

Thus, the entire top 10 moves about body linkage pivot 36 and cylinder pivot 30, as controlled by cylinder 28 and the three four-bar linkages described above. This Z-fold provides a more compact arrangement requiring less space within the vehicle body than prior arrangements, while also enabling the extended header to cover the folded top and eliminate the necessity of using a separate boot cover.

To enable this linear Z-type folding movement of top 10, accommodation must be made for lateral movement of the side linkage relative to the header. The mechanism 70 for enabling this lateral flexibility is shown in FIGS. 6 and 7. Middle rail extension 20 is pivoted at 72 to one flange 74 of bracket 66. The other bracket flange contains an elongated slot 76, which receives a stud 78 mounted on a pad 80 on header 12. The lost motion connection 70 causes the middle rail 18 and the remainder of the side linkages to move both pivotally and laterally with respect to the header 12. This movement enables the top 10 to fold in the above-described manner.

While only a preferred embodiment has been described and shown, obvious modifications are contemplated within the scope of this invention, as defined by the following claims.

We claim:

1. A convertible top for a vehicle, the vehicle having a storage compartment, the top comprising:

- a header;
- a pair of side linkages connected with the header;
- at least one crossbow extending between and connected with the side linkages;
- wherein the side linkages comprise:
 - a front rail;
 - a middle rail;
 - a rear rail;

a lost motion connection between the side linkages and the header to enable relative lateral movement of the side linkages during folding and unfolding of the top; and

wherein the top is foldable into a Z-shape into the storage compartment such that the header is not inverted, the header substantially covers the top, and the header substantially closes the storage compartment and wherein the middle and rear rails are inverted during folding of the top.

2. The convertible top of claim 1, wherein the side linkages include a 4-bar linkage to enable the Z-shaped fold.

3. The convertible top of claim 2, wherein the side linkages include a first side rail mounted on the header, a second side rail pivoted to the header, a third side rail pivotally connected to the vehicle and spaced upper and middle connecting links interconnecting the second and third side rails to form the 4-bar linkage.

4

4. The convertible top of claim 3, further including a lost motion connection between the second side rail and the header to enable lateral movement during folding and unfolding of the top.

5. The convertible top of claim 3, wherein the side linkages include an upper control arm interconnecting the upper connecting link and the header to form a second 4-bar linkage.

6. The convertible top of claim 5, wherein the side linkages include a lower control arm connecting the middle connecting link and the vehicle and a lower connecting link connecting the third side rail and the lower control arm to form a third 4-bar linkage.

7. The convertible top of claim 1, wherein the side linkages include two 4-bar linkages to enable the Z-folding action.

8. The convertible top of claim 7, wherein the side linkages include three 4-bar linkages.

9. The convertible top of claim 1 further comprising a plurality of links connecting the header, the front rail, the middle rail, the rear rail, and the crossbows.

10. A convertible top for a vehicle, the vehicle having a storage compartment, the top comprising:

- a header;
- a pair of side linkages connected with the header, the side linkages comprising a plurality of side rails;
- at least one crossbow extending between and connected with the side linkages;
- a lost motion connection between one of the side rails and the header so as to enable lateral movement of the side linkages during folding and unfolding of the top; and
- wherein the top is foldable into a Z-shape into the storage compartment such that the header is not inverted, the header substantially covers the top, and the header substantially closes the storage compartment.

11. The convertible top of claim 10, wherein the side linkages include a 4-bar linkage to enable the Z-shaped fold.

12. The convertible top of claim 11, wherein the side linkages include two 4-bar linkages to enable the Z-folding action.

13. The convertible top of claim 12, wherein the side linkages include three 4-bar linkages.

14. The convertible top of claim 10, wherein the side linkages include a first side rail mounted on the header, a second side rail pivoted to the header, a third side rail pivotally connected to the vehicle and spaced upper and middle connecting links interconnecting the second and third side rails to form the 4-bar linkage.

15. The convertible top of claim 14, wherein the side linkages include an upper control arm interconnecting the upper connecting link and the header to form a second 4-bar linkage.

16. The convertible top of claim 15, wherein the side linkages include a lower control arm connecting the middle connecting link and the vehicle body and a lower connecting link connecting the third side rail and the lower control arm to form a third 4-bar linkage.

17. The convertible top of claim 10, wherein the side linkages comprise a front rail, a middle rail, and a rear rail.

18. The convertible top of claim 17, wherein the middle and rear rails are inverted during folding of the top.

19. A convertible top for a vehicle, the vehicle having a storage compartment, the top comprising:

- a header;
- a pair of side linkages connected with the header;
- at least one crossbow extending between and connected with the side linkages;

5

a lost motion connection between one of the side rails and the header so as to enable lateral movement of the side linkages during folding and unfolding of the top; and wherein the top is foldable into a Z-shape into the storage compartment such that the header is not inverted, the

6

header substantially covers the top, and the header substantially closes the storage compartment.

* * * * *

DERWENT-ACC-NO: 2002-444714

DERWENT-WEEK: 200780

COPYRIGHT 2008 DERWENT INFORMATION LTD

TITLE: Folding convertible top with integral boot has
linkages
for movement between raised and lowered
positions

INVENTOR: HARRISON A W; HARRISON A W I ; HARRISON W ; RAWLINGS P ;
RAWLINGS S P

PATENT-ASSIGNEE: DURA CONVERTIBLE SYSTEMS INC[DURAN] , HARRISON A
W[HARRI], RAWLINGS S P[RAWLI]

PRIORITY-DATA: 2000US-242281P (October 20, 2000) , 2001WO-US49236
(October 20,
2001) , 2004US-415321 (April 7, 2004) , 2006US-603762 (November 22,
2006)

PATENT-FAMILY:

PUB-NO	PUB-DATE	LANGUAGE
WO 0243978 A2	June 6, 2002	EN
AU 200241660 A	June 11, 2002	EN
EP 1326758 A2	July 16, 2003	EN
JP 2004514590 W	May 20, 2004	JA
US 20040232721 A1	November 25, 2004	EN
EP 1326758 B1	June 8, 2005	EN
DE 60111404 E	July 14, 2005	DE
AU 2002241660 A8	September 15, 2005	EN
DE 60111404 T2	October 27, 2005	DE
US 7163255 B2	January 16, 2007	EN
US 20070063532 A1	March 22, 2007	EN
US 7300095 B2	November 27, 2007	EN

DESIGNATED-STATES: AE AG AL AM AT AU AZ BA BB BG BR BY BZ CA CH CN CO
CR CU CZ
DE DK DM DZ EE ES FI GB GD GE GH GM HR HU ID IL IN IS JP KE KG KP KR
KZ LC LK
LR LS LT LU LV MA MD MG MK MN MW MX MZ NO NZ PL PT RO RU SD SE SG SI
SK SL TJ
TM TR TT TZ UA UG US UZ VN YU ZA ZW AT BE CH CY DE DK EA ES FI FR GB
GH GM GR
IE IT KE LS LU MC MW MZ NL OA PT SD SE SL SZ TR TZ UG ZW AL AT BE CH
CY DE DK
ES FI FR GB GR IE IT LI LT LU LV MC MK NL PT RO SE SI TR DE GB

APPLICATION-DATA:

PUB-NO	APPL-DESCRIPTOR	APPL-NO
APPL-DATE		
WO2002043978A2	N/A	2001WO-US49236
October 20, 2001		
DE 60111404E	N/A	2001DE-611404
October 20, 2001		
DE 60111404T2	N/A	2001DE-611404
October 20, 2001		
EP 1326758A2	N/A	2001EP-988343
October 20, 2001		
EP 1326758B1	N/A	2001EP-988343
October 20, 2001		
EP 1326758A2	N/A	2001WO-US49236
October 20, 2001		
JP2004514590W	N/A	2001WO-US49236
October 20, 2001		
US20040232721A1	N/A	2001WO-US49236
October 20, 2001		
EP 1326758B1	N/A	2001WO-US49236
October 20, 2001		
DE 60111404E	N/A	2001WO-US49236
October 20, 2001		
DE 60111404T2	N/A	2001WO-US49236
October 20, 2001		
US 7163255B2	N/A	2001WO-US49236
October 20, 2001		
AU 200241660A	N/A	2002AU-041660
October 20, 2001		
AU2002241660A8	N/A	2002AU-241660
October 20, 2001		
JP2004514590W	N/A	2002JP-545934
October 20, 2001		
US20040232721A1	N/A	2004US-415321
April 7, 2004		
US 7163255B2	N/A	2004US-415321
April 7, 2004		
US20070063532A1	N/A	2006US-603762
November 22, 2006		
US 7300095B2	Based on	2006US-603762
November 22, 2006		

INT-CL-CURRENT:

TYPE	IPC	DATE
CIPP	B60J7/00	20060101
CIPS	B60J7/12	20060101
CIPS	B60J7/20	20060101

ABSTRACTED-PUB-NO: WO 0243978 A2

BASIC-ABSTRACT:

NOVELTY - The top has a pair of identical side linkages. Each side linkage comprises a front rail (16) that is secured and moves the header (12) of the top, a middle rail (18) connected to the front rail, and a rear rail (22) pivoted to a hydraulic cylinder which in turn is pivoted to a body mounting bracket (32). A lower control arm is pivoted to the bracket (32) and has an arm (38) pivoted to a lower connecting link (42) that is in turn pivoted to the rear rail. The upper end of the lower control arm is pivoted to the middle connection link (50) that is at one end pivoted to the middle rail and at the other end to the rear rail. The top folds to form a collapsed Z shape.

USE - Vehicle convertible top.

ADVANTAGE - The top does not require a separate boot for storage and incorporates a linkage that stores the top in compact configuration, with the outer surface of the header covering the remainder of the stored and folded top.

DESCRIPTION OF DRAWING(S) - The drawing shows a perspective view of the convertible top

Header (12)

Front rail (16)

Middle rail (18)

Rear rail (22)

Mounting bracket (32)

Arm (38)

Connection links (42, 50)

CHOSEN-DRAWING: Dwg.5/7

TITLE-TERMS: FOLD CONVERT TOP INTEGRAL BOOT LINK MOVEMENT RAISE LOWER
POSITION

DERWENT-CLASS: Q12

SECONDARY-ACC-NO:

Non-CPI Secondary Accession Numbers: 2002-350329